

Peacemaker Belt Magazine Pouch 005 (Black)

PM-MP005-BLK

GENERAL DESCRIPTION

The Peacemaker #PM-MP005-BLK magazine pouch is designed for Glock 22 .9mm magazines. The pouch features a single 50mm/2" belt loop with Velcro Hook retention.

DETAILS

Length: 145mm

Width: 70mm

Colour: Black

Finish: Denier 100% Polyester

Closure: Dual Snap & Velcro Hook & Loop

ROLL TOP LID

The pouch's lid features a moulded roll-top for a smooth, rounded closure and custom fit. Lid stays open leaving pouch accessible when empty and also features a black snap closure. The lid also contains an EVA foam insert for rigidity.

MATERIALS AND CONSTRUCTION

Shell Fabric: 900 Denier 100% Polyester

Shell Fabric: 900 Denier 100% Polyester, covering EVA plastic moulding.

Edge Binding: Nylon fabric edge binding

Finish: 900 Denier 100% Polyester

Nylon ends shall be fused or hot cut to prevent fraying.

CARRIAGE

Duty Belt: Nylon Modular Lightweight Load-carrying Equipment (MOLLE) system is used to attach #PM-MP005-BLK to standard 50mm/2" duty belt.

Covert Pouch Rail: Nylon Modular Lightweight Load-carrying Equipment (MOLLE) system is used to attach all operational pouches to #PMPR0001 Peacemaker Pouch Rail for covert operators.

CARE AND MAINTENANCE

Wash with damp cloth

Air dry

Do not tumble dry

Do not iron

Do not bleach



MATERIAL TESTING & STANDARDS

Pouch Material: 900 Denier 100% Polyester tested to and complied with the following:

- ISO 105-A02
- Colourfastness to Light AS 2001.4.21
- Colourfastness to Perspiration AS 2001.4.E04
- Colourfastness to Water AS 2001.4.E01
- Colourfastness to Rubbing As 2001.4.3
- Colourfastness to Washing AS 2001.4.15 Test K3
- Determination of Dimensional Stability AS 2001.5.4 Procedure 2 A Drying E
- Determination of Tear Strength Wing Rip As 2001.2.10
- Determination of Tensile Strength AS 2001.2.3.1
- Abrasion resistance AS 2001.2.25.2
- Ball Burst AS 2001.2.19
- pH Value determination of AS 2001.3.1 Test B
- No Presence of Formaldehyde ISO 14184.1
- No Presence of AZO Dyestuffs ISO 14362-1

