



PRODUCT NAME:

NavBoard® FlipLite™

PART NUMBER:
NB-FL02XX

PACKAGE INCLUDES:



NavBoard® FlipLite™



Adjustable friction hinge

PREPARE FLIPLITE FOR ATTACHING TO CARRIER



1 Push down on bungee lock to release



2 Flip up bungee lock and release. Open FlipLite.



3 Release the two mounting straps. FlipLite is ready for mounting.

ATTACHING THE FLIPLITE™ TO A PLATEFRAME MODULAR™ (PF-M™)



1 Feed the mounting straps through the uppermost slots.



2 Pull the mounting straps through the appropriate window (approximately 3" below the uppermost slots). Fold the FlipLite phone panel down.



3 Fold the mounting straps up and lock in by pushing down as shown above. Repeat with second strap.



4 Attach Velcro to back of device and pull corner retention straps over device to secure.



5 Fold bottom panel up and pull the closure over the bottom panel. The FlipLite™ is now attached and secured.



END USER INSTRUCTIONS - READ BEFORE USE

PRODUCT NAME:

NavBoard® FlipLite™

PART NUMBER:
NB-FL02XX

ATTACHING ZIPLITE™ TO ADVANCED TACTICAL HARNESS (ATH™)



1 Remove comfort foam. Feed the FlipLite straps through the uppermost slots.



2 Pull tabs through the bottom slots of the ATH™. Fold FlipLite down.



3 Fold the mounting straps up and lock in by pushing down as shown above.



4 Attach Velcro to back of device and pull corner retention straps over device to secure.



5 Fold bottom panel up and pull the closure over the bottom panel. The FlipLite™ is now attached and secured.